

# FAL PWT90



**Reference:** 870103

**Sizes:** 36 - 49

**Normative:**

EN ISO 20347:2022 / A:1:2024  
O7S+SR+CI+HI+HRO+FO+LG



## ESPECIFICACIONES

	Microfiber
	Closed buttress
	Slip resistance
	PS / Perforation resistance $\geq 1100\text{N}$ . Non-Metallic. Punch 3mm
	CI / Cold insulation of outsole complex
	HI / Heat insulation of outsole complex
	E / Energy absorption of heel up to 20J
	WR / Water resistance of whole footwear
	A / Antistatic footwear
	HRO / Resistant to hot contact
	SR / Slip resistance on ceramic tile floor with glycerine
	WPA / Resistant to water penetration and absorption
	FO / Hydrocarbon resistant sole
	LG / Ladder grip

## DESCRIPTION

### UPPER:

Water-repellent Putek® textile and microfiber.

### SOLE:

Rubber outsole and EVA midsole.

### PROTECTION ELEMENTS:

Perforation resistant (3 mm nail) textile insole.

### LINING:

Gore-Tex® waterproof + breathable membrane

### ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

### CLOSURE:

Water-repellent Laces.